

DERWENT ABSTRACT FOR: **JP 07-003083** (Mitsubishi), published 6 Jan 1995:

L2 ANSWER 5 OF 14 WPINDEX COPYRIGHT 2001 DERWENT INFORMATION LTD

ACCESSION NUMBER: 1995-078140 [11] WPINDEX

DOC. NO. CFI C1995-035202

TITLE: Prepn. of polyphenylene ether resin compsn. for non-yellowing resin compsn. - by pre-kneading component to exist also at interface between two different types of components, in specified compsn. contg. olefin, etc..

DERWENT CLASS: A12 A17 A25

PATENT ASSIGNEE(S): (MITP) MITSUBISHI PETROCHEMICAL CO LTD

COUNTRY COUNT: 1

PATENT INFORMATION:

PATENT NO	KIND	DATE	WEEK	LA	PG
JP 07003083	A	19950106	(199511)*	9	<--

APPLICATION DETAILS:

PATENT NO	KIND	APPLICATION	DATE
JP 07003083	A	JP 1993-143072	19930615

PRIORITY APPLN. INFO: JP 1993-143072 19930615

AN 1995-078140 [11] WPINDEX

AB JP 07003083 A UPAB: 19950322

Preparation is carried out by pre-kneading component (c) from where component (c) exists both in component (b) and at the interface between component (a) and component (b) in a composition containing 100 pts.wt. in total of (a) polyphenylene ether resin and (b) polyolefin and 2-50 pts.wt. of (c) hydrogenated aromatic alkenyl compound-conjugated diene block copolymer.

In the preparation of polyphenylene ether resin composition, 0.1-35 pts.wt. of (d) inorganic filler with mean particle size up to 1 microns is further added to 100 pts.wt. in total of component (a) and component (b) to make component (d) existing selectively in component (b) and/or component (c).

ADVANTAGE - The polyphenylene ether resin composition is widely used industrially because it has well balanced mechanical strength (e.g. bending elasticity, impact strength, etc.) and heat resistance.
Dwg.0/0